



| | | | | |
|----------------|---------------|------------|----------|--------|
| Sales Order No | Schedule Date | So Date | PO Num | Page |
| 569511 | | 12/15/2025 | TC166154 | 1 of 2 |

| | | | | |
|---|---|---|--------------------|---------------------|
| Featherlite Inc. P.O. Box 320 Highway 63 & 9 Cresco, IA 52136 563-547-6000 800-800-1230 salesdesk@fthr.com | BILL TO: 021587 THE MOTORCOACH STORE 5821 24TH STREET EAST BRADENTON, FL 34203 Phone: 941-896-4819 Fax: Sales Rep: STEVE BRITTAIN | SHIP TO: 021587 THE MOTORCOACH STORE 5821 24TH STREET EAST BRADENTON, FL34203 Phone: 941-896-4819 Fax: | | |
| F.O.B.: CRESCO, IA | Terms: 0% FCLP 2% NF 10 Days | Ship Via: FTHR TRANSPORTATION | | |
| Part Number | UM | Qty | Description | Retail Price |

Order Notes: DUPLICATE TC165332.

| | | | |
|---------------------------|-------------|---|------------------|
| 4414-026A-TC166154 | 1.00 | 4414 ENCLOSED CAR TRL BP STACKER | 98,336.00 |
| Revision No: 2 | | Vin: 4FG-A4263-6-TC166154 | |
| | | Width: 8.500 Length: 26.000 Height: 11.000 | |
| | | Gvwr: 18000 Tire Size: LT235/85R16(G) | |

INCLUDED IN STANDARD 4414-026A

Trailer Features

- 8'6" wide x 11'0" high x 26' long
- (3) 6.0K rubber torsion axles with electric brakes
- (6) 16" 8 hole silver aluminum wheels with GY LT235/85R16 LRG tires & hub covers
- Spread axle design w/ drop skirt and fenderettes
- Coupler 2.5/16" bolt on 25K w/22k Chains
- Single hydraulic jack with accessory equipment stored low in cabinet front wall
- Spare tire carrier box mounted on front of trailer tongue
- Spare tire included with matching spare tire and wheel
- (12) clear LED clearance lights
- (4) slimline LED stop/turn lights with center back up lights
- Rear spoiler
- Interlocking Smooth extruded aluminum floor
- 28" Beavertail
- 7' 6" high full width rear ramp, 2" thick with cable assist, stainless pressure latches, treadplate & vinyl hinge covers
- White .050 aluminum joggled side sheets
- Polished aluminum cast corners
- Ramp extension 16" full width 3/16" treadplate
- 42" HD 2" double sealed door on curbside
- Front winch plate in platform
- Skid plate underneath rear of trailer
- Flat nose w/ stainless steel vertical corners high with wrapped gravel guard low
- 1 5/8" side posts
- 1 5/8" wall insulation
- Mezzanine deck with capped stainless steel and non-slip surface. 54" of vertical height
- Camper step - slide out 36"
- (2) LED exterior load lights above rear ramp, switch located streetside at rear of trailer
- (3) recessed airliner tracks running front to back on mezzanine
- (2) surface mounted airliner tracks installed on lift load surface
- (2) recessed airliner tracks in main trailer floor close to fenderwells
- 14' auto lift with 6k capacity with wireless & wired controls. Release lever will be located on front of lift
- One piece aluminum bolt-on extension for automotive lift
- Drop in center aluminum panels for enclosing middle of auto lift
- Run hot lead to rear frame for back up camera with access through a removable panel

CONSISTING OF THE FOLLOWING OPTIONS

| | | | | |
|--------------------------------------|------|-------|--|------------------|
| 4414026AB | EA | 1.00 | 4414 26' enclosed stacker car trailer - 8'6" W x 11'0" H | 88,952.00 |
| SUBTOTAL FOR STANDARD OPTIONS | | | | 88,952.00 |
| 00626 | A EA | 8.00 | Additional clearance light clear lens (ea) 4 EXTRA PER SIDE. CENTER ACCORDINGLY. | 480.00 |
| 00673 | A EA | 1.00 | Exterior LED Lighting Package: Includes a pair of surface mount scene lights with switch by camper door (9" x 7" 12-Volt, 5000 Lumens) | 1,831.00 |
| 00618 | A EA | 1.00 | Premium escape door with removable inner fender and built in step - Triple axle trailers (4410-032A, & 4414) | 6,293.00 |
| 00680 | A FT | 26.00 | Black Exterior Side Sheets (Per/ft of trailer) | 780.00 |
| SUBTOTAL FOR ADDED OPTIONS | | | | 9,384.00 |

| | | | |
|---------------------------|-------------|---|------------------|
| L414-026A-TI166154 | 1.00 | 4414 INTERIOR | 25,304.00 |
| Revision No: 1 | | Vin: 4FG-A4263-4-TI166154 | |
| | | Width: 8.500 Length: 26.000 Height: 11.000 | |
| | | Gvwr: 18000 Tire Size: LT235/85R16(G) | |

INCLUDED IN STANDARD L414-026A

